



US011364653B1

(12) **United States Patent**  
**Voss et al.**

(10) **Patent No.:** **US 11,364,653 B1**  
(45) **Date of Patent:** **Jun. 21, 2022**

(54) **DEVICE FOR STAINING OR PAINTING PLANKS**

(56) **References Cited**

(71) Applicant: **StainTrac, LLP**, Tulsa, OK (US)  
(72) Inventors: **Duane Carl Voss**, Inola, OK (US);  
**Clifford Marion Richison**, Tulsa, OK (US);  
**Joshua Mikal Burrup**, Broken Arrow, OK (US)

U.S. PATENT DOCUMENTS  
2,015,768 A \* 10/1935 Thompson ..... B44D 3/225  
118/208  
2,489,445 A \* 11/1949 Benzuly ..... B05B 13/0207  
118/305  
3,319,601 A \* 5/1967 Baker ..... B05C 9/06  
118/255

(73) Assignee: **STAINTRAC, LLP**, Tulsa, OK (US)

(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 102 days.

FOREIGN PATENT DOCUMENTS

CN 203540847 4/2014  
CN 103623977 12/2015

(Continued)

(21) Appl. No.: **16/901,615**

*Primary Examiner* — Binu Thomas

(22) Filed: **Jun. 15, 2020**

(74) *Attorney, Agent, or Firm* — James F. Lea, III; Gable Gotwals

**Related U.S. Application Data**

(60) Provisional application No. 62/861,049, filed on Jun. 13, 2019.

(51) **Int. Cl.**  
**B05B 13/02** (2006.01)  
**B05C 1/08** (2006.01)  
**B05C 9/04** (2006.01)  
**B05C 1/02** (2006.01)  
**B05B 13/04** (2006.01)  
**B27K 5/02** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **B27K 5/02** (2013.01); **B05B 13/02** (2013.01); **B05B 13/0436** (2013.01); **B05C 1/025** (2013.01); **B05C 1/08** (2013.01); **B05C 1/083** (2013.01); **B05C 9/04** (2013.01)

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(57) **ABSTRACT**

A device for staining or painting planks has an enclosure and a plank receiver for guiding a plank into the enclosure. At least one pair of vertical rollers are provided for engaging the plank received in the plank receiver. A lever may be positioned to contact the plank upon exit from the plank receiver. A linkage bar is affixed to the lever and to vertical rollers. Moving the lever by insertion of the plank moves the vertical rollers in preparation for receiving a leading edge of the plank. The vertical rollers are mounted on swing arms for facilitating adjustment of a space between the left vertical rollers and the right vertical rollers for accommodating planks of various thicknesses. Vertical sprayers are pivotally mounted and in communication with the swing arms for pivoting with the vertical rollers for maintaining a constant distance between the vertical rollers and the left vertical sprayer.

**16 Claims, 5 Drawing Sheets**

